

SOLVENT DISTILLATION EQUIPMENT

LS Series[†] Two stage Distillation Process:

1. Heats solvent to a vapor state
2. Cools and converts vapor to a pure, reusable liquid product



LS-Jr.-E

- Small shop applications

Process rate	3-5 gal/shift*
Boiling Range	100 - 300°F



LS-55E with JetVac

- Safely recovers high boiling solvents with JetVac option

Process rate	55 gal/shift*
Boiling Range	100 - 500°F

*Varies with application

†Equipment appearance may vary slightly from photo

FTI's Unique Features:

Eliminate or reduce solvent-based waste

• 99+% pure, reusable solvent

• Patented design and encapsulated heating element

• CSA approved

• Non-stick coated boiling chamber for quick clean up

• Stilbags or Stilpans available to aid in residue removal

• Solvent boiling range 100 to 300°F. Increases to 500°F with vacuum assist. All units vacuum capable.

• Technical support from FTI via toll free number



LS-15IIE

- Single batch recovery industrial duty

Process rate	15 gal/shift*
Boiling Range	100 - 300°F



Little Cooler

- Provides a closed loop water supply to the condenser where a water source is not readily available.



Before



After



FINISH THOMPSON INC.

921 Greenegarden Road • Erie, PA 16501-1291 U.S.A.
Ph 814-851-4478 • Fax 814-851-8518
E-mail: fti@finishthompson.com • www.finishthompson.com

Thousands installed worldwide.